

# LOT DETAILS

Market Support - Surplus Sales | Lot 24.20 | Total Quantity (PCS): 655,990

## Lot Summary

|                 |                                                               |                   |                                                  |
|-----------------|---------------------------------------------------------------|-------------------|--------------------------------------------------|
| Warehouse       | Los Angeles, California                                       | Categories        | Opto Devices                                     |
| Number of Items | 49                                                            | Total Quantity    | 655,990 PCS                                      |
| Pallet Weight   | 1,102.0 lb (499.9 kg)                                         | Pallet Dimensions | 48.0 x 44.0 x 71.0 in (121.9 x 111.8 x 180.3 cm) |
| Sales Term      | Complete pallet lot; sold as-is; all sales final; no returns. | Lot               | Lot 24.20                                        |

## Items

| #  | Part Number    | Brand | Category        | Package | Outline | Cartons | Quantity | Datasheet | Description                                                                                                                                              |
|----|----------------|-------|-----------------|---------|---------|---------|----------|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1  | 4N37.300-QT-C  | QT    | Optoelectronics | C       | DIP-6   | 2       | 18,750   | 4N37.300  | Optocouplers,Phototransistor Output,VDE0884,CTR >=100%,IF=60mA,Vceo >=30V,Viso >=5300Vrms,Vio=1500V,Vce(Sat) <=0.3V, in DIP-6 PKG.                       |
| 2  | 4N38-QT-C      | QT    | Optoelectronics | C       | DIP-6   | 1       | 9,800    | 4N38      | Optocouplers,Phototransistor Output,CTR 20~100%,Vceo >=80V,Viso >=5300Vrms,Vce(Sat) <=1.0V, in DIP-6 PKG                                                 |
| 3  | 5082-7650-QT-C | QT    | Optoelectronics | C       | S43V4   | 1       | 1,325    | -         | Single Digit Display, GaAsP, Red, 630nm, Red Face, typ. 840ucd(If=5mA), C.A.                                                                             |
| 4  | CNY17-3-QT-C   | QT    | Optoelectronics | C       | DIP-6   | 1       | 4,950    | CNY17-3   | Optocouplers/TR Output, CTR 100~200%, Vceo >=70V, Viso >=5300Vrms, Vce(Sat) <=0.4V, Typical ton=10us, toff=10us, in DIP-6                                |
| 5  | CNY17F-3-QT-C  | QT    | Optoelectronics | C       | DIP-6   | 1       | 6,500    | CNY17F-3  | Optocouplers/TR Output/GaAs Input, CTR 100~200%, Vceo >=70V, Viso >=5300Vrms, Vce(Sat) <=0.4V, Typical ton=10us, toff=10us, No Base Connection, in DIP-6 |
| 6  | CNY17F-4-QT-C  | QT    | Optoelectronics | C       | DIP-6   | 1       | 700      | CNY17F-4  | Optocouplers/TR Output/GaAs Input, CTR 160~320%, Vceo >=70V, Viso >=5300Vrms, Vce(Sat) <=0.4V, Typical ton=10us, toff=10us, No Base Connection, in DIP-6 |
| 7  | FLV110-QT-B    | QT    | Optoelectronics | B       | -       | 2       | 22,250   | -         | 5mm Round (T-1 3/4), Cut Flange, Red, Bright(GaAsP, 660nm), Color Diffused, typ. 3mcd (10ma), 60 degree Viewing Angle                                    |
| 8  | H11A2-QT-C     | QT    | Optoelectronics | C       | DIP-6   | 1       | 450      | H11A2     | Optocouplers/TR Output, CTR>=20%, Vceo>=30V, Vce(Sat)<=0.4V, Iceo<=50ns, Viso>=5300VAC(rms), 1 min. Typical Ton=2us, Toff=2us, in DIP-6                  |
| 9  | H11AA1-QT-C    | QT    | Optoelectronics | C       | DIP-6   | 3       | 11,100   | H11AA1    | Optocouplers/TR Output/AC Input, CTR>=20%, Vceo>=30V, Vce(Sat)<=0.4V, Iceo<=50nA, Viso>=5300VAC(rms), 1 min, in DIP-6 package                            |
| 10 | H11AA2-QT-C    | QT    | Optoelectronics | C       | DIP-6   | 1       | 7,500    | H11AA2    | Optocouplers/TR Output/AC Input, CTR>=10%, Vceo>=30V, Vce(Sat)<=0.4V, Iceo<=200nA, Viso>=5300VAC(rms), 1 min, in DIP-6 package                           |
| 11 | H11B1-QT-C     | QT    | Optoelectronics | C       | DIP-6   | 3       | 20,400   | H11B1     | Optocouplers/Darlington Output, CTR >=500%, Vceo >=25V, Viso >=5300Vrms, Vce(Sat) <=1.0V, in DIP-6                                                       |
| 12 | H11B2-QT-C     | QT    | Optoelectronics | C       | DIP-6   | 1       | 4,500    | H11B2     | Optocouplers/Darlington Output, CTR >=200%, Vceo >=25V, Viso >=5300Vrms, Vce(Sat) <=1.0V, in DIP-6                                                       |
| 13 | H11D2-QT-C     | QT    | Optoelectronics | C       | DIP-6   | 2       | 8,000    | H11D2     | High Voltage Optocouplers/TR Output/GaAs Input, CTR >=20%, Vceo >=300V, Viso >=5300Vrms, Vce(Sat) <=0.4V, in DIP-6                                       |
| 14 | H11G2-QT-C     | QT    | Optoelectronics | C       | DIP-6   | 2       | 17,900   | H11G2     | High Voltage Optocouplers/Darlington Output/GaAs Input, CTR >=1000%, Vceo >=80V, Viso >=5300Vrms, Vce(Sat) <=1.0V, in DIP-6                              |
| 15 | H22A3-QT-C     | QT    | Optoelectronics | C       | -       | 1       | 50       | -         | Optical Interrupter Switches, IF=20mA, VCE=5V, On-State Collector Current 4mA, BVCEO Min. 30v, Lead Spacing Typical 0.284                                |

| #  | Part Number     | Brand | Category        | Package | Outline   | Cartons | Quantity | Datasheet | Description                                                                                                                                                                           |
|----|-----------------|-------|-----------------|---------|-----------|---------|----------|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 16 | HCPL-2530-QT-C  | QT    | Optoelectronics | C       | DIP-8     | 2       | 18,950   | HCPL-2530 | Optocouplers/Dual High Speed Transistor Output/AlGaAs Input, Viso >=2500Vrms, Ift=7.0mA,Vcc=30V,Vcc out=4.5V,Vol=0.5V, Typical Tphl=1.5us,Tplh=1.5us, in DIP-8                        |
| 17 | HCPL-2601-QT-C  | QT    | Optoelectronics | C       | DIP-8     | 3       | 28,000   | HCPL-2601 | Optocouplers/Very High Speed Logic Gate Output, Viso >=2500Vrms, Typical Data Rate=10Mbit/s, Output Current TTL-loads=8.0, Propogation Delay Time Tphl=0.075ns,Tplh=0.075ns, in DIP-8 |
| 18 | HCPL-2611-QT-C  | QT    | Optoelectronics | C       | DIP-8     | 1       | 7,650    | HCPL-2611 | Optocouplers/Very High Speed Logic Gate Output, Viso >=2500Vrms, Typical Data Rate=10Mbit/s, Output Current TTL-loads=8.0, Propogation Delay Time Tphl=0.075ns,Tplh=0.075ns, in DIP-8 |
| 19 | HCPL-2730-QT-C  | QT    | Optoelectronics | C       | DIP-8     | 2       | 11,700   | HCPL-2730 | Optocouplers/Dual Split Darlington Output/AlGaAs Input, Viso >=2500Vrms, Ift=1.6mA,Vcc=7.0V,Vol=0.4V, Typical Tphl=20us,Tplh=35+us, in DIP-8                                          |
| 20 | HLMP-1700-QT-B  | QT    | Optoelectronics | B       | -         | 2       | 38,000   | -         | 3mm Round (T-1) Small Flange with Stand-Off, Red (GaAsP, 635nm), Color Diffused, typ. 2mcd (2ma), 50 degree Viewing Angle                                                             |
| 21 | HLMP-1790-QT-B  | QT    | Optoelectronics | B       | -         | 1       | 4,750    | -         | 3mm Round (T-1) Small Flange with Stand-Off, Green (GaP, 565nm), Color Diffused, typ. 2mcd (2ma), 50 degree Viewing Angle                                                             |
| 22 | HLMP-3300-QT-B  | QT    | Optoelectronics | B       | -         | 1       | 5,500    | -         | 5mm Round (T-1 3/4), Cut Flange, Red (GaAsP, 635nm), Color Diffused, typ. 10mcd (10ma), 45 degree Viewing Angle                                                                       |
| 23 | HLMP-3850A-QT-B | QT    | Optoelectronics | B       | R5        | 3       | 52,250   | -         | 5mm(T-1 3/4) Round,Cut Flange with Stopper, Yellow LED,PL=585nm,150mcd(Typ)at 20mA, 24 Degree,in Bulk Packing                                                                         |
| 24 | HLMP-4719-QT-B  | QT    | Optoelectronics | B       | -         | 1       | 3,500    | -         | 5mm Round (T-1 3/4) with Stopper, Yellow(GaAsP, 585nm), Color Diffused, typ. 2mcd (2ma), 25 degree Viewing Angle                                                                      |
| 25 | HLMP-6620-QT-B  | QT    | Optoelectronics | B       | C0808     | 1       | 1,000    | -         | SMD LF Type,1.78mm Round,5V Resistor,Axial Straight,Hi-Eff Red LED,626nm,2.0mcd(Typ),90 Degree,in Bulk Pack,Non-RoHS                                                                  |
| 26 | HLMP-D150A-QT-B | QT    | Optoelectronics | B       | R5        | 1       | 500      | -         | 5mm Round (T-1 3/4) with Cut Flange, Red (GaAlAs, 660nm), Color Diffused, typ. 3mcd(1ma), 65 degree Viewing Angle                                                                     |
| 27 | HLMP-K402-QT-B  | QT    | Optoelectronics | B       | R3        | 1       | 1,000    | -         | 3mm Round (T-1), Small Flange, Stand-Off, Orange 612nm, Color Diffused, typ. 6.5mcd(10ma), 90 degree Viewing Angle                                                                    |
| 28 | HLMP-K600-QT-B  | QT    | Optoelectronics | B       | -         | 1       | 1,250    | -         | 3mm Round (T-1), Small Flange, Stand-Off, Green (GaP, 560nm), Color Diffused, typ. 4.5mcd (10ma), 90 degree Viewing Angle                                                             |
| 29 | MCT2-QT-C       | QT    | Optoelectronics | C       | DIP-6     | 1       | 500      | MCT2      | Optocouplers/TR Output, CTR >=20%, Vceo >=30V, Viso >=5300Vrms, Vce(Sat) <=0.4V, in DIP-6                                                                                             |
| 30 | MCT2.300-QT-C   | QT    | Optoelectronics | C       | DIP-6     | 3       | 29,600   | MCT2.300  | Optocouplers/TR Output-VDE0884, CTR >=20%, Vceo >=30V, Viso >=5300Vrms, Vce(Sat) <=0.4V, in DIP-6                                                                                     |
| 31 | MCT5211-QT-C    | QT    | Optoelectronics | C       | DIP-6     | 1       | 10,000   | MCT5211   | Optocouplers/TR Output/AlGaAs Input, CTR >=150%, Vceo >=30V, Viso >=5300Vrms, Vce(Sat) <=0.4V, in DIP-6                                                                               |
| 32 | MCT6-QT-C       | QT    | Optoelectronics | C       | DIP-8     | 7       | 61,000   | MCT6      | Multichannel Optoisolators/TR Output, CTR >60%, Vio >=2800Vrms, Vceo >70V, Vce(Sat)<0.3V, Typical ton/toff=6.0us, in DIP-8                                                            |
| 33 | MCT9001-QT-C    | QT    | Optoelectronics | C       | DIP-8     | 2       | 19,700   | MCT9001   | Dual Phototransistor Optocoupler, CTR 50~600%, Vf=1.0V, Viso >=4000Vdc, Vce(Sat) <=0.4V, Typical ton=3.0us, toff=3.0us, in DIP-8                                                      |
| 34 | MOC3012-QT-C    | QT    | Optoelectronics | C       | DIP-6     | 1       | 500      | -         | Optocoupler -Traic Output (120VAC), Ift<=5mA, Vdrm=250V, Idrm<=100nA, Itsm=1A@1ms, Vtm<=3V, Ih(typ)=100uA, Viso >7500VAC(pk) in DIP-6                                                 |
| 35 | MOC3021-QT-C    | QT    | Optoelectronics | C       | DIP-6     | 3       | 7,200    | -         | Optocoupler -Traic Output (240VAC), Ift<=15mA, Vdrm=400V, Idrm<=100nA, Itsm=1A@1ms, Vtm<=3V, Ih(typ)=100uA, Viso >7500VAC(pk) in DIP-6                                                |
| 36 | MOC3023-QT-C    | QT    | Optoelectronics | C       | DIP-6     | 8       | 43,650   | -         | Optocoupler -Traic Output (240VAC), Ift<=5mA, Vdrm=400V, Idrm<=100nA, Itsm=1A@1ms, Vtm<=3V, Ih(typ)=100uA, Viso >7500VAC(peak) in DIP-6                                               |
| 37 | MV53124A-QT-B   | QT    | Optoelectronics | B       | 3.8X6.3MM | 1       | 14,250   | -         | 3.8x6.3mm Rectangular Legend with Reflector, Super Yellow LED, GaAsP, 585nm, 6.0mcd (Typ.)at 20mA, Color Diffused, 100 degree Viewing Angle, in Bulk Packing                          |

| #  | Part Number         | Brand | Category        | Package | Outline | Cartons | Quantity | Datasheet | Description                                                                                                                                    |
|----|---------------------|-------|-----------------|---------|---------|---------|----------|-----------|------------------------------------------------------------------------------------------------------------------------------------------------|
| 38 | <b>MV5353-QT-B</b>  | QT    | Optoelectronics | B       | R5      | 1       | 6,500    | -         | 5mm (T-1 3/4) Round, Cut Flange, Super Yellow LED, GaAsP, 585nm, 15mcd (Typ.)at 20mA, Color Diffused, 65 degree Viewing Angle, in Bulk Packing |
| 39 | <b>MV5453-QT-B</b>  | QT    | Optoelectronics | B       | R5      | 6       | 74,250   | -         | 5mm (T-1 3/4) Round , Cut Flange, Green LED, GaP, 565nm, 20mcd(Tpy.) at 20mA, Color Diffused, 75 degree Viewing Angle, in Bulk Packing         |
| 40 | <b>MV57164-QT-C</b> | QT    | Optoelectronics | C       | C1004   | 1       | 240      | -         | 10 Bar Graph Display, GaAsP Red, Hi-Eff 630nm, Gray, typ. 510mcd(If=10mA),                                                                     |
| 41 | <b>MV5752-QT-B</b>  | QT    | Optoelectronics | B       | R5      | 1       | 11,500   | -         | 5mm (T-1 3/4) Round, Cut Flange, Deep Red LED, GaAsP, 635nm, 100mcd(Tpy.) at 20mA, Color Tinted, 28 degree Viewing Angle, in Bulk Packing      |
| 42 | <b>MV5753-QT-B</b>  | QT    | Optoelectronics | B       | R5      | 3       | 22,500   | -         | 5mm (T-1 3/4) Round, Cut Flange, Deep Red LED, GaAsP, 635nm, 15mcd (Tpy.) at 20mA, Color Diffused, 65 degree Viewing Angle, in Bulk Packing    |
| 43 | <b>MV6353-QT-B</b>  | QT    | Optoelectronics | B       | R5      | 1       | 15,250   | -         | 5mm (T-1 3/4) Round, Cut Flange, Super Yellow LED, GaAsP, 585nm, 15mcd(Tpy.) at 20mA, Color Diffused, 65 degree Viewing Angle, in Bulk Packing |
| 44 | <b>MV64521-QT-B</b> | QT    | Optoelectronics | B       | R5      | 1       | 1,250    | -         | 5mm (T-1 3/4) Round , Cut Flange, Green LED, GaP, 565nm, 100mcd(Tpy.) at 20mA, Color Tinted, 35 degree Viewing Angle, in Bulk Packing          |
| 45 | <b>MV6700-QT-B</b>  | QT    | Optoelectronics | B       | C0809   | 1       | 1,000    | -         | SMD,LF Type,1.78mm Round,Axial Straight, Deep Red LED,GaAsP,635nm,3.0mcd(Tpy.) at 10mA,50 Degree,in Bulk Packing, Non-RoHS                     |
| 46 | <b>MV6753-QT-B</b>  | QT    | Optoelectronics | B       | R5      | 2       | 17,750   | -         | 5mm (T-1 3/4) Round, Cut Flange, Deep Red LED, GaAsP, 635nm, 15mcd (Tpy.) at 20mA, Color Diffused, 65 degree Viewing Angle, in Bulk Packing    |
| 47 | <b>MV8410-QT-B</b>  | QT    | Optoelectronics | B       | R5      | 1       | 1,000    | -         | 5mm (T-1 3/4) Round , Cut Flange, Green LED, GaP, 565nm, 240mcd(Tpy.) at 20mA, Water Clear, 12 degree Viewing Angle, in Bulk Packing           |
| 48 | <b>MV9102-QT-B</b>  | QT    | Optoelectronics | B       | RA      | 1       | 125      | -         | 10mm Small flange round led, Red LED, GaAsP, 660nm, 2400mcd(Tpy.) at 20mA, Water Clear, 8 degree Viewing Angle, in Bulk Packing                |
| 49 | <b>SL5511-QT-C</b>  | QT    | Optoelectronics | C       | DIP-6   | 1       | 10,000   | SL5511    | Optocouplers/TR Output, CTR 25~400%, Vceo >=30V, Viso >=5300Vrms, Vce(Sat) <=0.4V, Typical ton=20us,toff=50us, in DIP-6                        |

## Terms of Sale

**All sales are final.** Products are sold as-is, as complete pallet lots, with no returns. Bids are based on ex-warehouse terms. The buyer is responsible for freight, pickup, export/import requirements, taxes, duties, and applicable handling or compliance costs. Availability is subject to prior sale, bid acceptance, and final confirmation by Taitron Components.