

LOT DETAILS

Market Support - Surplus Sales | Lot 24.22 | Total Quantity (PCS): 254,725

Lot Summary

Warehouse	Los Angeles, California	Categories	Semiconductors, Opto Devices
Number of Items	128	Total Quantity	254,725 PCS
Pallet Weight	456.0 lb (206.8 kg)	Pallet Dimensions	48.0 x 42.0 x 64.0 in (121.9 x 106.7 x 162.6 cm)
Sales Term	Complete pallet lot; sold as-is; all sales final; no returns.	Lot	Lot 24.22

Items

#	Part Number	Brand	Category	Package	Outline	Cartons	Quantity	Datasheet	Description
1	4N27.SD-QT-T	QT	Optoelectronics	T	SOP-6	3	3,000	4N27.SD	Optocouplers,Phototransistor Output,CTR >=10%,IF=80mA,Vceo >=30V,Viso >=5300Vrms,VF=1.2V(Typ.),Vio>=1500V,Vce(Sat) <=0.5V,in SOP-6 PKG
2	4N28.SD-QT-T	QT	Optoelectronics	T	SOP-6	6	11,000	4N28.SD	Optocouplers,Phototransistor Output,CTR >=10%,IF=80mA,Vceo >=30V,Viso >=5300Vrms,VF=1.2V(Typ.),Vio>=500V,Vce(Sat) <=0.5V,in SOP-6 PKG
3	4N33.SD-QT-T	QT	Optoelectronics	T	SOP-6	3	5,000	4N33.SD	Optocouplers,PhotoDarlington Output,CTR >=500%,IF=80mA,Vceo >=30V,Viso >=5300Vrms,VF=1.2V(Typ.),Vio>=1500V,Vce(Sat) <=1.0V, in SOP-6 PKG.
4	4N35.SD-QT-T	QT	Optoelectronics	T	SOP-6	14	56,000	4N35.SD	Optocouplers,Phototransistor Output,CTR >=100%,IF=60mA,Vceo >=30V,Viso >=5300Vrms,Vio=3550V,Vce(Sat) <=0.3V, in SOP-6 PKG.
5	4N36.SD-QT-T	QT	Optoelectronics	T	SOP-6	3	9,000	4N36.SD	Optocouplers,Phototransistor Output,CTR >=100%,IF=60mA,Vceo >=30V,Viso >=5300Vrms,Vio=2500V,Vce(Sat) <=0.3V, in SOP-6 PKG.
6	4N37.SD-QT-T	QT	Optoelectronics	T	SOP-6	2	6,000	4N37.SD	Optocouplers,Phototransistor Output,CTR >=100%,IF=60mA,Vceo >=30V,Viso >=5300Vrms,Vio=1500V,Vce(Sat) <=0.3V, in SOP-6 PKG.
7	4N39.SD-QT-T	QT	Optoelectronics	T	SOP-6	2	3,000	4N39.SD	Optocouplers,SCR Output,VDE0884,IF=60mA,Viso >=5300Vrms,VF=1.1V(Typ.),Vdm=200V,in SOP-6 PKG
8	5KP7.0A/4-GSI-T30	GSI, General Semiconductor	Discrete	T30	T6L	1	800	5KP5.0A	5000W 7.0Vwm 5% Uni-dir TVS in T6L
9	6N135.200D-QT-T	QT	Optoelectronics	T	DIP-8	1	5,000	6N135.200D	Optocouplers,High Speed 1MBd,CTR >=7%,IF=25mA,Viso >=2500Vrms,VF=1.5V(Typ.),Vcc=4.5V,Vo=0.4V,tPHL=1.5uS(Max.),in DIP-8 PKG
10	6N137.200D-QT-T	QT	Optoelectronics	T	SIP-8	1	3,000	6N137.200D	Optocouplers,High Speed 10MBd,Logic Gate,IF=20mA,Viso>=2500Vrms,VF=1.55V(Typ.),tPHL=75ns(Max.),tPLH=75ns(Max.),in SIP-8 PKG.
11	6N138.200D-QT-T	QT	Optoelectronics	T	DIP-8	1	5,000	6N138.200D	Optocouplers,High Gain Split,Darlington Output,CTR >=300%,IF=20mA,Viso>=2500Vrms,VF=1.45V(Typ.),Vce(Sat)<=0.4V,tPHL=10us(Max.), DIP-8 PKG
12	CNY28-QT-C	QT	Optoelectronics	C	-	1	200	-	Optical Interrupter Switches, IF=20mA, VCE=5V, On-State Collector Current Min 0.02mA, BVCEO Min 30V, Lead Spacing Typical 0.284
13	CNY29-QT-C	QT	Optoelectronics	C	-	1	100	-	Optical Interrupter Switches, IF=20mA, VCE=5V, On-State Collector Current Min 2.5mA, BVCEO Min 25V, Lead Spacing Typical 0.284
14	CQX16-QT-B	QT	Optoelectronics	B	TO-46	1	200	-	940 nm AlGaAs INFRARED LED
15	CQX17-QT-B	QT	Optoelectronics	B	TO-46	1	200	-	940 nm AlGaAs INFRARED LED
16	FND318C-QT-C	QT	Optoelectronics	C	S36V0	1	150	-	0.362 INCH RED 7 SEGMENT DISPL
17	GMC8975C-QT-B	QT	Optoelectronics	B	C1309	1	25	-	1.2' 5 x 7 Green CC Dot Matrix

#	Part Number	Brand	Category	Package	Outline	Cartons	Quantity	Datasheet	Description
18	H21A6-QT-C	QT	Optoelectronics	C	-	1	100	-	Optical Interrupter Switches, IF=20mA, VCE=5V, On-State Collector Current Min 4mA, BVCEO Min 55V, Lead Spacing Typical 0.284
19	H21B6-QT-C	QT	Optoelectronics	C	-	1	400	-	Optical Interrupter Switches, IF=10mA, VCE=1.5V, On-State Collector Current Min 25mA, BVCEO Min 55V, Lead Spacing Typical 0.284
20	H22A4-QT-C	QT	Optoelectronics	C	-	1	100	-	Optical Interrupter Switches, IF=20mA, VCE=5V, On-State Collector Current 1mA, BVCEO Min. 55v, Lead Spacing Typical 0.284
21	H22A5-QT-C	QT	Optoelectronics	C	-	1	100	-	Optical Interrupter Switches, IF=20mA, VCE=5V, On-State Collector Current 2mA, BVCEO Min. 55v, Lead Spacing Typical 0.284
22	HLMP-0301-QT-B	QT	Optoelectronics	B	-	1	250	-	2.54x7.24mm Rectangular, Red, Deep (GaAsP, 635nm), Color Diffused, typ. 5mcd(20ma), 100 degree Viewing Angle
23	HLMP-0401-QT-B	QT	Optoelectronics	B	-	1	500	-	2.54x7.24mm Rectangular, Yellow (GaAsP, 585nm), Color Diffused, typ. 5mcd (20ma), 100 degree Viewing Angle
24	HLMP-0503-QT-B	QT	Optoelectronics	B	-	1	750	-	2.54x7.24mm Rectangular, Green (GaP, 565nm), Color Diffused, typ. 3mcd(20ma), 100 degree Viewing Angle
25	HLMP-1700-QT-B	QT	Optoelectronics	B	-	1	6,500	-	3mm Round (T-1) Small Flange with Stand-Off, Red (GaAsP, 635nm), Color Diffused, typ. 2mcd (2ma), 50 degree Viewing Angle
26	HLMP-1719-QT-B	QT	Optoelectronics	B	-	1	3,000	-	3mm Round (T-1) Small Flange with Stand-Off, Yellow (GaAsP, 585nm), Color Diffused, typ. 2mcd (2ma), 50 degree Viewing Angle
27	HLMP-3300-QT-B	QT	Optoelectronics	B	-	1	1,000	-	5mm Round (T-1 3/4), Cut Flange, Red (GaAsP, 635nm), Color Diffused, typ. 10mcd (10ma), 45 degree Viewing Angle
28	HLMP-3301-QT-B	QT	Optoelectronics	B	-	1	3,000	-	5mm Round (T-1 3/4), Cut Flange, Red (GaAsP, 635nm), Color Diffused, typ. 10mcd (10ma), 45 degree Viewing Angle
29	HLMP-3850A-QT-B	QT	Optoelectronics	B	R5	1	500	-	5mm(T-1 3/4) Round,Cut Flange with Stopper,Yellow LED,PL=585nm,150mcd(Typ)at 20mA, 24 Degree,in Bulk Packing
30	HLMP-6305.GR-QT-T	QT	Optoelectronics	T	C0808	1	3,000	-	SMD LF Type,1.78mm Round,G-Bend,Hi-Eff Red LED,626nm,12mcd(Typ)at 10mA,28 Degree,in Reel Pack,Non-RoHS
31	HLMP-6305.YR-QT-T	QT	Optoelectronics	T	C0808	1	1,200	-	SMD LF Type,1.78mm Round,Y-Bend,Hi-Eff Red LED,626nm,12mcd(Typ)at 10mA,28 Degree,in Reel Pack,Non-RoHS
32	HLMP-6405-QT-B	QT	Optoelectronics	B	C0808	1	1,000	-	SMD LF Type,1.78mm Round,Axial Straight,Yellow LED,585nm,12mcd(Typ)at 10mA,28 Degree,in Bulk Pack,Non-RoHS
33	HLMP-6405.YR-QT-T	QT	Optoelectronics	T	C0808	1	1,200	-	SMD LF Type,1.78mm Round,Y-Bend,Yellow LED,585nm,12mcd(Typ)at 10mA,28 Degree,in Reel Pack,Non-RoHS
34	HLMP-6405.ZR-QT-T	QT	Optoelectronics	T	C0808	1	3,600	-	SMD LF Type,1.78mm Round,Z-Bend,Yellow LED,585nm,12mcd(Typ)at 10mA,28 Degree,in Reel Pack,Non-RoHS
35	HLMP-6600.GR-QT-T	QT	Optoelectronics	T	C0808	1	3,000	-	SMD LF Type,1.78mm Round,5V Resistor,G-Bend,Hi-Eff Red LED,626nm,5.0mcd(Typ),90 Degree,in Reel Pack, Non-RoHS
36	HLMP-6600.YR-QT-T	QT	Optoelectronics	T	C0808	1	2,400	-	SMD LF Type,1.78mm Round,5V Resistor,Y-Bend,Hi-Eff Red LED,626nm,5.0mcd(Typ),90 Degree,in Reel Pack,Non-RoHS
37	HLMP-6620.GR-QT-T	QT	Optoelectronics	T	C0808	1	3,000	-	SMD LF Type,1.78mm Round,5V Resistor,G-Bend,Hi-Eff Red LED,626nm,2.0mcd(Typ),90 Degree,in Reel Pack, Non-RoHS
38	HLMP-6620.YR-QT-T	QT	Optoelectronics	T	C0808	1	2,400	-	SMD LF Type,1.78mm Round,5V Resistor,Y-Bend,Hi-Eff Red LED,626nm,2.0mcd(Typ),90 Degree,in Reel Pack,Non-RoHS
39	HLMP-6720.YR-QT-T	QT	Optoelectronics	T	C0808	1	2,400	-	SMD LF Type,1.78mm Round,5V Resistor,Y-Bend,Yellow LED,585nm,5.0mcd(Typ),90 Degree,in Reel Pack,Non-RoHS
40	HLMP-6800.YR-QT-T	QT	Optoelectronics	T	C0808	1	2,400	-	SMD LF Type,1.78mm Round,5V Resistor,Y-Bend,Green LED,569nm,5.0mcd(Typ),90 Degree,in Reel Pack,Non-RoHS
41	HLMP-6800.ZR-QT-T	QT	Optoelectronics	T	C0808	1	3,600	-	SMD LF Type,1.78mm Round,5V Resistor,Z-Bend,Green LED,569nm,5.0mcd(Typ),90 Degree,in Reel Pack,Non-RoHS
42	HLMP-6820.ZR-QT-T	QT	Optoelectronics	T	C0808	1	3,600	-	SMD LF Type,1.78mm Round,5V Resistor,Z-Bend,Green LED,569nm,2.0mcd(Typ),90 Degree,in Reel Pack,Non-RoHS
43	HLMP-7000.GR-QT-T	QT	Optoelectronics	T	C0808	1	3,600	-	SMD LF Type,1.78mm Round,G-Bend,Hi Eff Red LED,626nm,0.6mcd(Typ)at 2mA,90 Degree,in Reel Pack,Non-RoHS

#	Part Number	Brand	Category	Package	Outline	Cartons	Quantity	Datasheet	Description
44	HLMP-7000.YR-QT-T	QT	Optoelectronics	T	C0808	1	2,400	-	SMD LF Type,1.78mm Round,Y-Bend,Hi-Eff Red LED,626nm,0.6mcd(Typ)at 2mA,90 Degree,in Reel Pack,Non-RoHS
45	HLMP-7019.YR-QT-T	QT	Optoelectronics	T	C0808	1	2,400	-	SMD LF Type,1.78mm Round,Y-Bend,Yellow LED,585nm,0.6mcd(Typ)at 2mA,90 Degree,in Reel Pack,Non-RoHS
46	HLMP-7040.YR-QT-T	QT	Optoelectronics	T	C0808	1	2,400	-	SMD LF Type,1.78mm Round,Y-Bend,Green LED,569nm,0.6mcd(Typ)at 2mA,90 Degree,in Reel Pack,Non-RoHS
47	HLMP-D105A-QT-B	QT	Optoelectronics	B	R5	1	500	-	5mm Round (T-1 3/4) with Cut Flange, Red, Hyper(GaAlAs, 645nm), Water Clear, typ. 240mcd(20ma), 24 degree Viewing Angle
48	HLMP-D400-QT-B	QT	Optoelectronics	B	R5	1	500	-	5mm Round (T-1 3/4) with Cut Flange, Orange, 612nm, Color Diffused, typ. 3.5mcd(10ma), 60 degree Viewing Angle
49	HLMP-K101-QT-B	QT	Optoelectronics	B	R3	1	250	-	3mm Round (T-1), Small Flange, Stand-Off, Red, Bright(GaAlAs, 660nm), Color Diffused, typ. 45mcd(20ma), 60 degree Viewing Angle
50	HLMP-K105-QT-B	QT	Optoelectronics	B	R3	1	4,750	-	3mm Round (T-1), Small Flange, Stand-Off, Red, Bright(GaAlAs, 660nm), Water Clear, typ. 70mcd(20ma), 35 degree Viewing Angle
51	HLMP-K155-QT-B	QT	Optoelectronics	B	R3	1	250	-	3mm Round (T-1), Small Flange, Stand-Off, Red, Bright(GaAlAs, 660nm), Water Clear, typ. 3mcd(1ma), 45 degree Viewing Angle
52	HLMP-K400-QT-B	QT	Optoelectronics	B	R3	1	1,000	-	3mm Round (T-1), Small Flange, Stand-Off, Orange, 612nm, Color Diffused, typ. 4mcd(10ma), 90 degree Viewing Angle
53	HLMP-K401-QT-B	QT	Optoelectronics	B	R3	1	500	-	3mm Round (T-1), Small Flange, Stand-Off, Orange, 612nm, Color Diffused, typ. 5mcd(10ma), 90 degree Viewing Angle
54	HLMP-K640-QT-B	QT	Optoelectronics	B	-	1	1,500	-	3mm Round (T-1), Small Flange, Stand-Off, Green (GaP, 560nm), Water Clear, typ. 4.2mcd (20ma), 45 degree Viewing Angle
55	HLMP-M251-QT-B	QT	Optoelectronics	B	-	1	1,500	-	4mm flat top red/green/yellow
56	LED55BF-QT-B	QT	Optoelectronics	B	TO-46	1	500	-	940 nm AlGaAs INFRARED LED
57	LED56-QT-B	QT	Optoelectronics	B	TO-46	1	500	-	940 nm AlGaAs INFRARED LED
58	MP22(PAIR)-QT-B	QT	Optoelectronics	B	-	1	3,000	-	MP22(PAIR)
59	MR5310-QT-B	QT	Optoelectronics	B	-	1	1,000	-	T-3/4 integrated resistor w/ro
60	MR5361-QT-B	QT	Optoelectronics	B	R3	1	250	-	3mm Round (T-1), Small Flange with Stand-Off, Super Yellow LED, AlInGaP, 585nm, 4mcd(Typ.) at 12mA, Color Diffused, 60 degree Viewing Angle, in Bulk Packing
61	MR5461-QT-B	QT	Optoelectronics	B	R3	1	250	-	3mm Round (T-1), Small Flange with Stand-Off, Green LED, GaP, 565nm, 4mcd(Typ.) at 12mA, Color Diffused, 60 degree Viewing Angle, in Bulk Packing
62	MR5660-QT-B	QT	Optoelectronics	B	R3	1	500	-	3mm Round (T-1) Small Flange with Stand-Off, Hyper Red LED, GaAsP, 660nm, 1.5mcd(Typ.) at 5mA, White Diffused, 60 degree Viewing Angle, in Bulk Packing
63	MV50154-QT-B	QT	Optoelectronics	B	R5	2	1,500	-	5mm (T-1 3/4) Round , Cut Flange, Red LED, GaAsP, 660nm, 1.5mcd(Tpy.) at 10mA, Color Diffused, 50 degree Viewing Angle, in Bulk Packing
64	MV5023A-QT-B	QT	Optoelectronics	B	R5	1	4,750	-	5mm (T-1 3/4) Round , with Stopper, Red LED, GaAsP, 660nm, 1.6mcd(Tpy.) at 20mA, Color Diffused, 80 degree Viewing Angle, in Bulk Packing
65	MV5024A-QT-B	QT	Optoelectronics	B	R5	1	3,000	-	5mm (T-1 3/4) Round , with Stopper, Red LED, GaAsP, 660nm, 3.0mcd(Tpy.) at 20mA, Color Diffused, 40 degree Viewing Angle, in Bulk Packing
66	MV5052-QT-B	QT	Optoelectronics	B	R5	1	250	-	5mm (T-1 3/4) Round , Cut Flange, Red LED, GaAsP, 660nm, 1.0mcd(Tpy.) at 20mA, Color Tinted, 72 degree Viewing Angle, in Bulk Packing
67	MV5054A1-QT-B	QT	Optoelectronics	B	R5	1	250	-	5mm (T-1 3/4) Round , Cut Flange, Red LED, GaAsP, 660nm, 1.5mcd(Tpy.) at 10mA, Color Diffused, 24 degree Viewing Angle, in Bulk Packing

#	Part Number	Brand	Category	Package	Outline	Cartons	Quantity	Datasheet	Description
68	MV5152-QT-B	QT	Optoelectronics	B	R5	1	250	-	5mm (T-1 3/4) Round, Cut Flange, Deep Red LED, GaAsP, 635nm, 100mcd (Typ.) at 20mA, Color Tinted, 28 degree Viewing Angle, in Bulk Packing
69	MV5153-QT-B	QT	Optoelectronics	B	R5	1	4,750	-	5mm (T-1 3/4) Round, Cut Flange, Deep Red LED, GaAsP, 635nm, 15mcd (Typ.) at 20mA, Color Diffused, 65 degree Viewing Angle, in Bulk Packing
70	MV53642-QT-B	QT	Optoelectronics	B	R3	1	3,000	-	3mm (T-1) Round, Small Flange with Stand-Off, Super Yellow LED, GaAsP, 585nm, 4.5mcd (Typ.) at 10mA, Color Diffused, 70 degree Viewing Angle, in Bulk Packing
71	MV53BL-QT-B	QT	Optoelectronics	B	-	1	750	-	T-3/4 ROUND BASE RED/GREEN/YEL
72	MV54643-QT-B	QT	Optoelectronics	B	R3	1	1,750	-	3mm (T-1) Round, Small Flange with Stand-Off, Green LED, GaP, 565nm, 5mcd(Typ.) at 20mA, Color Diffused, 75 degree Viewing Angle, in Bulk Packing
73	MV5477C-QT-B	QT	Optoelectronics	B	R3	1	3,500	-	3mm (T-1) Round, Cut flange, Green LED, GaP, 565nm, 7mcd(Typ.) at 20mA, color diffused, 180 degree Viewing Angle, in Bulk Packing
74	MV57640-QT-B	QT	Optoelectronics	B	R3	1	5,750	-	3mm Round (T-1) Small Flange with Stand-Off, Deep Red LED, GaAsP, 635nm, 2.0mcd (Typ.) at 10mA, Color Diffused, 60 degree Viewing Angle, in Bulk Packing
75	MV57BL-QT-B	QT	Optoelectronics	B	-	1	12,250	-	5mm Round (T-1 3/4), red/green/yellow
76	MV6000-QT-B	QT	Optoelectronics	B	-	1	500	-	5mm T-3/4 Square base, diffused
77	MV6352-QT-B	QT	Optoelectronics	B	R5	1	2,500	-	5mm (T-1 3/4) Round, Cut Flange, Super Yellow LED, GaAsP, 585nm, 90mcd(Typ.) at 20mA, Color Tinted, 28 degree Viewing Angle, in Bulk Packing
78	MV6400-QT-B	QT	Optoelectronics	B	C0809	1	8,000	-	SMD LF type, 1.78mm Round, Green LED,Axial Straight, 569nm, 3.0mcd(Typ.) at 10mA, 90 Degree, in Bulk Pack, Non-RoHS
79	MV64520-QT-B	QT	Optoelectronics	B	R5	1	500	-	5mm (T-1 3/4) Round , Cut Flange, Green LED, GaP, 565nm, 25mcd(Typ.) at 20mA, Color Tinted, 35 degree Viewing Angle, in Bulk Packing
80	MV64530-QT-B	QT	Optoelectronics	B	R5	1	3,750	-	5mm (T-1 3/4) Round , Cut Flange, Green LED, GaP, 565nm, 3.0mcd(min.)/20mcd(Typ.) at 20mA, Color Diffused, 65 degree Viewing Angle, in Bulk Packing
81	MV6752-QT-B	QT	Optoelectronics	B	R5	1	1,000	-	5mm (T-1 3/4) Round, Cut Flange, Deep Red LED, GaAsP, 635nm, 100mcd (Typ.) at 20mA, Color Tinted, 28 degree Viewing Angle, in Bulk Packing
82	MV8140-QT-B	QT	Optoelectronics	B	R5	1	500	-	5mm (T-1 3/4) Round , Cut Flange, Red LED, GaAsP, 660nm, 220mcd(Typ.) at 20mA, Water Clear, 40 degree Viewing Angle, in Bulk Packing
83	MV8190-QT-B	QT	Optoelectronics	B	R5	1	250	-	5mm (T-1 3/4) Round , Cut Flange, Red LED, GaAsP, 660nm, 100mcd(Typ.) at 20mA, Color Diffused, 40 degree Viewing Angle, in Bulk Packing
84	MV8303-QT-B	QT	Optoelectronics	B	R5	1	250	-	5mm (T-1 3/4) Round , Cut Flange, Yellow LED, GaAsP, 590nm, 940mcd(Typ.) at 20mA, Water Clear, 20 degree Viewing Angle, in Bulk Packing
85	MV9101-QT-B	QT	Optoelectronics	B	RA	1	400	-	10mm Small flange round led, Red LED, GaAsP, 660nm, 1500mcd(Typ.) at 20mA, Water Clear, 8 degree Viewing Angle, in Bulk Packing
86	OPB703-QT-B	QT	Optoelectronics	B	-	1	50	-	PHOTOTRANSISTOR OUTPUT REFLECT
87	OPB704-QT-B	QT	Optoelectronics	B	-	1	50	-	PHOTOTRANSISTOR OUTPUT REFLECT
88	OPB705-QT-B	QT	Optoelectronics	B	-	1	100	-	PHOTOTRANSISTOR OUTPUT REFLECT
89	OPB705W-QT-B	QT	Optoelectronics	B	-	1	100	-	PHOTOTRANSISTOR OUTPUT REFLECT
90	OPB860N11-QT-C	QT	Optoelectronics	C	-	1	100	-	Optical Interrupter Switches, IF=20mA, VCE=5V, On-State Collector Current Min 0.5mA, BVCEO Min 30V, Lead Spacing Typical 0.32
91	OPB860N55-QT-C	QT	Optoelectronics	C	-	1	50	-	PHOTOTRANSISTOR OUTPUT OPTICAL
92	OPB860T51-QT-C	QT	Optoelectronics	C	-	1	100	-	Optical Interrupter Switches, IF=20mA, VCE=5V, On-State Collector Current Min 0.5mA, BVCEO Min 30V, Lead Spacing Typical 0.32

#	Part Number	Brand	Category	Package	Outline	Cartons	Quantity	Datasheet	Description
93	OPB861N51-QT-C	QT	Optoelectronics	C	-	1	100	-	Optical Interrupter Switches, IF=10mA, VCE=5V, On-State Collector Current Min 1.0mA, BVCEO Min 30V, Lead Spacing Typical 0.32
94	OPB861N55-QT-C	QT	Optoelectronics	C	-	1	50	-	Optical Interrupter Switches, IF=10mA, VCE=5V, On-State Collector Current Min 1.0mA, BVCEO Min 30V, Lead Spacing Typical 0.32
95	OPB861T51-QT-C	QT	Optoelectronics	C	-	1	100	-	Optical Interrupter Switches, IF=10mA, VCE=5V, On-State Collector Current Min 1.0mA, BVCEO Min 30V, Lead Spacing Typical 0.32
96	OPB861T55-QT-C	QT	Optoelectronics	C	-	1	50	-	PHOTOTRANSISTOR OUTPUT OPTICAL
97	OPB862T55-QT-C	QT	Optoelectronics	C	-	1	150	-	Optical Interrupter Switches, IF=20mA, VCE=0.6V, On-State Collector Current Min 1.8mA, BVCEO Min 30V, Lead Spacing Typical 0.32
98	OPB865N11-QT-C	QT	Optoelectronics	C	-	1	50	-	PHOTOTRANSISTOR OUTPUT OPTICAL
99	OPB865T11-QT-C	QT	Optoelectronics	C	-	1	100	-	Optical Interrupter Switches, IF=20mA, VCE=5.0V, On-State Collector Current Min 0.5mA, BVCEO Min 30V, Lead Spacing Typical 0.22
100	OPB866N51-QT-C	QT	Optoelectronics	C	-	1	50	-	Optical Interrupter Switches, IF=10mA, VCE=5.0V, On-State Collector Current Min 1.0mA, BVCEO Min 30V, Lead Spacing Typical 0.22
101	OPB866T55-QT-C	QT	Optoelectronics	C	-	1	50	-	PHOTOTRANSISTOR OUTPUT OPTICAL
102	OPB867N51-QT-C	QT	Optoelectronics	C	-	1	100	-	Optical Interrupter Switches, IF=20mA, VCE=0.6V, On-State Collector Current Min 1.8mA, BVCEO Min 30V, Lead Spacing Typical 0.22
103	OPB867N55-QT-C	QT	Optoelectronics	C	-	1	200	-	Optical Interrupter Switches, IF=20mA, VCE=0.6V, On-State Collector Current Min 1.8mA, BVCEO Min 30V, Lead Spacing Typical 0.22
104	OPB867T51-QT-C	QT	Optoelectronics	C	-	1	50	-	PHOTOTRANSISTOR OUTPUT OPTICAL
105	OPB867T55-QT-C	QT	Optoelectronics	C	-	1	50	-	Optical Interrupter Switches, IF=20mA, VCE=0.6V, On-State Collector Current Min 1.8mA, BVCEO Min 30V, Lead Spacing Typical 0.22
106	QED422-QT-B	QT	Optoelectronics	B	TO-46	1	1,000	-	5mm Infrared Round LED, T-1 3/4, Standard Type with Small Flange, GaAlAs 880nm, Purple, Vf typ. 1.7v(If=100mA), Power min. 10mW/sr, 60 degree
107	QED423-QT-B	QT	Optoelectronics	B	TO-46	1	1,500	-	5mm Infrared Round LED, T-1 3/4, Standard Type with Small Flange, GaAlAs 880nm Purple, Vf typ. 1.7v(If=100mA), Power min 18mW/sr, 60 degree
108	QPE1259(PAIR)-QT-B	QT	Optoelectronics	B	-	1	500	-	QPE1259(PAIR)
109	QRC1113-QT-B	QT	Optoelectronics	B	-	1	100	-	Reflective Objective Sensor with NPN Phototransistor output for .150" Optimum Response
110	QSD128-QT-B	QT	Optoelectronics	B	R5-BK	1	500	-	IR Photo Transistor, 5mm Round, 880nm, +-12 degrees, Ic(0n)>=1.6mA, 7us in T1 3/4 Package
111	QSE123-QT-B	QT	Optoelectronics	B	SS	1	500	-	Phototransistor silicon infrare
112	QVA11123-QT-C	QT	Optoelectronics	C	-	1	200	-	PHOTOTRANSISTOR OUTPUT OPTICAL
113	QVA11133-QT-C	QT	Optoelectronics	C	-	1	200	-	PHOTOTRANSISTOR OUTPUT OPTICAL
114	QVA11223-QT-C	QT	Optoelectronics	C	-	1	200	-	PHOTOTRANSISTOR OUTPUT OPTICAL
115	QVA11224-QT-C	QT	Optoelectronics	C	-	1	1,000	-	PHOTOTRANSISTOR OUTPUT OPTICAL
116	QVA11323-QT-C	QT	Optoelectronics	C	-	1	200	-	PHOTOTRANSISTOR OUTPUT OPTICAL
117	QVA11333-QT-C	QT	Optoelectronics	C	-	1	100	-	PHOTOTRANSISTOR OUTPUT OPTICAL
118	QVA21113-QT-C	QT	Optoelectronics	C	-	1	200	-	PHOTOTRANSISTOR OUTPUT OPTICAL
119	QVA21114-QT-C	QT	Optoelectronics	C	-	1	150	-	PHOTOTRANSISTOR OUTPUT OPTICAL
120	QVA21213-QT-C	QT	Optoelectronics	C	-	1	200	-	PHOTOTRANSISTOR OUTPUT OPTICAL
121	QVA21314-QT-C	QT	Optoelectronics	C	-	1	150	-	PHOTOTRANSISTOR OUTPUT OPTICAL
122	QVB11134-QT-C	QT	Optoelectronics	C	-	1	50	-	PHOTOTRANSISTOR OUTPUT OPTICAL
123	QVB11233-QT-C	QT	Optoelectronics	C	-	1	200	-	Optical Interrupter Switches, IF=20mA, VCE=5.0V, On-State Collector Current Min 0.5mA, BVCEO Min 30V, Lead Spacing Typical 0.3

#	Part Number	Brand	Category	Package	Outline	Cartons	Quantity	Datasheet	Description
124	QVB11323-QT-C	QT	Optoelectronics	C	-	1	200	-	Optical Interrupter Switches, IF=20mA, VCE=5.0V, On-State Collector Current Min 0.2mA, BVCEO Min 30V, Lead Spacing Typical 0.32
125	QVB21213-QT-C	QT	Optoelectronics	C	-	1	150	-	Optical Interrupter Switches, IF=20mA, VCE=5.0V, On-State Collector Current Min 0.1mA, BVCEO Min 30V, Lead Spacing Typical 0.3
126	QVB21214-QT-C	QT	Optoelectronics	C	-	1	200	-	Optical Interrupter Switches, IF=20mA, VCE=5.0V, On-State Collector Current Min 0.2mA, BVCEO Min 30V, Lead Spacing Typical 0.3
127	QVB21314-QT-C	QT	Optoelectronics	C	-	1	200	-	Optical Interrupter Switches, IF=20mA, VCE=5.0V, On-State Collector Current Min 0.2mA, BVCEO Min 30V, Lead Spacing Typical 0.32
128	TLN-G3R5-24150-QT-B	QT	Optoelectronics	B	R5	1	1,750	-	5mm (T-1 3/4) Round , Cut Flange, Green LED, GaP, 565nm, 150mcd(Tpy.) at 20mA, Color Diffused, 24 degree Viewing Angle, in Bulk Packing

Terms of Sale

All sales are final. Products are sold as-is, as complete pallet lots, with no returns. Bids are based on ex-warehouse terms. The buyer is responsible for freight, pickup, export/import requirements, taxes, duties, and applicable handling or compliance costs. Availability is subject to prior sale, bid acceptance, and final confirmation by Taitron Components.